



FREDERICK COUNTY GOVERNMENT

Jan H. Gardner
County Executive

DIVISION OF FINANCE

Department of Procurement & Contracting

Lori L. Depies, CPA, Division Director
Diane Fouche, CPPB, Director

June 12, 2017
Invitation For Bid #17-402
Ferric Storage Tank
Addendum #1

This addendum contains revisions, clarifications, and information pertinent to the Invitation For Bid (IFB) for the title project and shall supplement, amend, and become part of the solicitation. All responses shall be based on the solicitation TOGETHER with this Addendum.

Acknowledgment of this addendum shall be submitted with the response. Failure to acknowledge addenda may subject the Contractor to disqualification.

Bids are due **June 21, 2017 at 3:00 PM.**

REVISIONS:

1. In Attachment 8 "INSURANCE REQUIREMENTS", DELETE the requirements for pollution liability coverage.

CLARIFICATIONS:

1. The tank will be used to store Liquid Aluminum Sulfate (see attachment 1)
2. In accordance with the bid documents the tank must pass a Hydrostatic leak test with a tank full of clean water. The water will be allowed to stand for 24 hours to verify leakage. A successful test does not relieve the Contractor of liability. Final acceptance will not be granted until the tank is filled by the County with Aluminum Sulfate and it is verified that there are no leaks.
3. Contractors should be aware that if there would be a spill due to poor installation, their insurance may not provide them coverage and the County will pursue the Contractor directly to recoup its losses.
4. The existing ladder will be reused and not need to be replaced.

ATTACHMENTS:

1. Safety Data sheet for Liquid Alum
2. Mandatory pre-bid sign in sheet

Except as noted herein, all terms and conditions of the document referenced, as heretofore changed, remain unchanged and in full force and effect.

Brian Stieg, Project Manager IV
Department of Procurement & Contracting



Liquid Alum

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 08/09/16 Date of Issue: 05/01/15

Version: 1.4

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Liquid Alum

Alternate Name: Aluminum Sulfate, Liquid

Formula: $\text{Al}_2(\text{SO}_4)_3 \cdot 14 \text{H}_2\text{O}$ (Dry Equivalent)

Intended Use of the Product

Alum is used as a coagulating agent in municipal and industrial water and wastewater treatment and as an additive in papermaking.

Name, Address, and Telephone of the Responsible Party

Manufacturer

CHEMTRADE LOGISTICS INC.

155 Gordon Baker Road

Suite 300

Toronto, Ontario M2H 3N5

For SDS Info: (416) 496-5856

www.chemtradelogistics.com

Emergency Telephone Number

Emergency Number :

Canada: CANUTEC +1-613-996-6666 / US: CHEMTREC +1-800-424-9300

Chemtrade Emergency Contact: (866) 416-4404

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC – Day or Night

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290

Skin Corr. 1A H314

Eye Dam. 1 H318

Aquatic Acute 3 H402

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



GHS05

Signal Word (GHS-US) :

Danger

Hazard Statements (GHS-US) :

H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H402 - Harmful to aquatic life

Precautionary Statements (GHS-US) :

P234 - Keep only in original container.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Liquid Alum

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a doctor.

P321 - Specific treatment (see section 4 on this SDS).

P363 - Wash contaminated clothing before reuse.

P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	30 - 60	Not classified
Sulfuric acid, aluminum salt (3:2)	(CAS No) 10043-01-3	30 - 60	Met. Corr. 1, H290 Eye Dam. 1, H318 Aquatic Acute 3, H402

*As $\text{Al}_2(\text{SO}_4)_3 \cdot 14 \text{H}_2\text{O}$ (Dry Aluminum Sulfate).

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200]. A range of concentration as prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Rinse immediately with plenty of water. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage.

Inhalation: May cause respiratory irritation.

Skin Contact: Redness. Pain. Serious skin burns. Blisters.

Eye Contact: Redness. Pain. Blurred vision. Severe burns. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Liquid Alum

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reactivity: Hazardous reactions will not occur under normal conditions. Liquid alum may react with some metals, to give flammable, potentially explosive hydrogen gas. Hydrogen gas can accumulate to explosive concentrations inside confined spaces.

Advice for Firefighters

Precautionary Measures Fire: Not available

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Forms aluminum oxide, sulfur dioxide and/or sulfur trioxide at temperatures above 760°C (1400°F) or when dry alum is encompassed in a fire involving other burning materials.

Other Information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (dust, vapor, mist, gas).

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Collect spillage. Dispose in a safe manner in accordance with local/national regulations.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Use good housekeeping practices during storage, transfer, handling, to avoid excessive dust accumulation. Protect from moisture.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong bases.

Special Rules on Packaging: Store in original container or corrosive resistant and/or lined container.

Specific End Use(s)

For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing.

Liquid Alum

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved dust mask if dust has the potential to become airborne.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, light green, slight yellow, brow, amber, or orange like tint
Odor	: Odorless
Odor Threshold	: Not available
pH	: 1.4 - 2.6
Melting Point	: Not applicable
Freezing Point	: -15.56 °C (4°F)
Boiling Point	: 101 °C (213.80 °F)
Flash Point	: Not flammable
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.30 - 1.35
Solubility	: Water: Completely miscible in water.
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions. Liquid alum may react with some metals, to give flammable, potentially explosive hydrogen gas. Hydrogen gas can accumulate to explosive concentrations inside confined spaces.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials. Moisture.

Incompatible Materials: Strong bases. Metals.

Hazardous Decomposition Products: Oxides of aluminum. The decomposition products are corrosive and hazardous to health.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

pH: 1.4 - 2.6

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 1.4 - 2.6

Respiratory or Skin Sensitization: Not classified

Liquid Alum

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Redness. Pain. Serious skin burns. Blisters.

Symptoms/Injuries After Eye Contact: Redness. Pain. Blurred vision. Severe burns. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Water (7732-18-5)	
LD50 Oral Rat	> 90000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified

Persistence and Degradability Not available

Bioaccumulative Potential Not available

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ALUMINUM SULFATE)
Hazard Class : 8
Identification Number : UN3264
Label Codes : 8
Packing Group : III
ERG Number : 154



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ALUMINUM SULFATE)
Hazard Class : 8
Identification Number : UN3264
Packing Group : III
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B



Liquid Alum

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ALUMINUM SULFATE)
Packing Group : III
Identification Number : UN3264
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (CONTAINS ALUMINUM SULFATE)
Packing Group : III
Hazard Class : 8
Identification Number : UN3264
Label Codes : 8



SECTION 15: REGULATORY INFORMATION



US Federal Regulations

Liquid Alum	
Clean Water Act	
Ingredient Name	Reportable Quantities
Aluminum sulfate (10043-01-3)	5000 lb (2270 kg)
Liquid Alum	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

US State Regulations

Liquid Alum	
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Canadian Regulations

Liquid Alum	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
 	
Water (7732-18-5)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class E - Corrosive Material

Liquid Alum

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 08/09/16
Revision Summary : Section 1
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life

Party Responsible for the Preparation of This Document

CHEMTRADE LOGISTICS, INC.

For SDS Info: (416) 496-5856

Handle product with due care and avoid unnecessary contact. This information is supplied under U.S. OSHA'S "Right to Know" (29 CFR 1910.1200) and Canada's WHMIS regulations. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The information contained herein is based on data available to us and is believed to be true and accurate but it is not offered as a product specification. No warranty, expressed or implied, regarding the accuracy of this data, the hazards connected with the use of the product, or the results to be obtained from the use thereof, is made and Chemtrade and its affiliates assume no responsibility. Chemtrade is a member of the CIAC (Chemistry Industry Association of Canada) and adheres to the codes and principles of Responsible Care™.



Chemtrade North America SDS Template

May 30, 2017

IFB #17-402

Ferric/Aluminum Sulfate Storage Tank

MANDATORY Pre-Bid Conference
2:00 PM, Eastern Standard Time (EST)
Ballenger-McKinney Wastewater Treatment Plant
7400 Marcies Choice Lane, Frederick, MD 21704

FIRM NAME: COASTAL TECH. SALES
Representative: CHARLES SEGER
Address: 116 KEYSTONE DR. MONTGOMERYVILLE PA 18936
Email Address: CHARLES@COASTALTECHNICAL.COM
Phone No.: 215 678-1965 **FAX No.:** 215 678-1649

FIRM NAME: ENVIRONMENTAL SOLUTIONS-CBR, INC.
Representative: JOHN SPRECHER
Address: 4728 DORSEY HALL DR, #801, ELLICOTT CITY, MD 21042
Email Address: JOHN@ES-CBR.COM
Phone No.: 410-375-6154 **FAX No.:** 410-964-3321

FIRM NAME: EMH ENVIRONMENTAL INC
Representative: EO HALL
Address: 3060 WASHINGTON RD. GLADWOOD, MD 21738
Email Address: emh@emhenviro.com
Phone No.: 410-489-9430 **FAX No.:** 410-489-9925

FIRM NAME: M2 Construction LLC
Representative: Jamie Harbell
Address: PO Box 39 Landisville PA 17538
Email Address: Jharbell@m2constructionllc.com
Phone No.: (717) 365-8801 **FAX No.:** (717) 823-6979